

Wall 7



Designed to be used where the aesthetics of the light fitting, along with a tough robust construction is needed. The fittings are IP65 and IK8 compliant, supplied complete with an opal diffuser for even light distribution. Available in emergency and non emergency versions, the latter having a super-slim profile.

- Genuine replacement for 70W Metal Halide & Sodium
- Fully encapsulated IP65 TUV Certified Driver
- High impact polycarbonate lens
- Up to 65% energy saving
- 50000 hours Options
- Photocell version complete with Lucy Zodium miniature photocell (55 lux)
- Emergency / Emergency Photocell version
- Asymmetric product available on request



Part Code	Description / Spec								Power	Lumens	Temp
DLWL30	DayLux™ Wall 7 30W								30W	2550	4200
Driver Fixed	IP 65	CRI 80	Kg	Height 309mm	Width 264mm	Depth 115mm	Length	Dia	Cutout		
DLWL30PC	DayLux™ Wall 7 30W with Photocell								30W	2550	4200
Driver Fixed	IP 65	CRI 80	Kg	Height 309mm	Width 264mm	Depth 115mm	Length	Dia	Cutout		
DLWL30/E3	DayLux™ Wall 7 30W Emergency								30W	2550	4200
Driver Fixed	IP 65	CRI 80	Kg	Height 309mm	Width 264mm	Depth 182mm	Length	Dia	Cutout		
DLWL30PC/E3	DayLux™ Wall 7 30W with Photocell & Emergency								30W	2550	4200
Driver Fixed	IP 65	CRI 80	Kg	Height 309mm	Width 264mm	Depth 182mm	Length	Dia	Cutout		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.