

## Cylinder 5



- Die-cast aluminium body designed to provide optimal thermal control with aluminium bezel and aluminium reflector
- Surface high performance downlight with efficacy up to 129 Llm/cW with gloss reflector
- Surface, suspension and BESA mounted
- Matt and Gloss reflector options



Part Code	Description / Spec								Power	Lumens	Temp
DLCYG16	DayLux™ Cylinder 5 Gloss 13w								13W	1600	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG16/E3	DayLux™ Cylinder 5 Gloss 13w Emergency								13W	1600	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG16/DIM	DayLux™ Cylinder 5 Gloss 13w DALI and Switch Dim								13W	1600	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG16/DIM/E3	DayLux™ Cylinder 5 Gloss 13w DALI and Switch Dim & Emergency								13W	1600	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG22	DayLux™ Cylinder 5 Gloss 17w								17W	2200	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG22/E3	DayLux™ Cylinder 5 Gloss 17w Emergency								17W	2200	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG22/DIM	DayLux™ Cylinder 5 Gloss 17w DALI and Switch Dim								17W	2200	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG22/DIM/E3	DayLux™ Cylinder 5 Gloss 17w DALI and Switch Dim & Emergency								17W	2200	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG32	DayLux™ Cylinder 5 Gloss 25w								25W	3200	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG32/E3	DayLux™ Cylinder 5 Gloss 25w Emergency								25W	3200	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		

**Cylinder 5 cont.**

Part Code	Description / Spec								Power	Lumens	Temp
DLCYG32/DIM	DayLux™ Cylinder 5 Gloss 25w DALI and Switch Dim								25W	3200	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG32/DIM/E3	DayLux™ Cylinder 5 Gloss 25w DALI and Switch Dim & Emergency								25W	3200	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYG63	DayLux™ Cylinder 5 Gloss 52w								52W	6300	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM16	DayLux™ Cylinder 5 Matt 13w								13W	1600	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM16/E3	DayLux™ Cylinder 5 Matt 13w Emergency								13W	1600	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM16/DIM	DayLux™ Cylinder 5 Matt 13w DALI and Switch Dim								13W	1600	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM16/DIM/E3	DayLux™ Cylinder 5 Matt 13w DALI and Switch Dim & Emergency								13W	1600	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM22	DayLux™ Cylinder 5 Matt 17w								17W	2200	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM22/E3	DayLux™ Cylinder 5 Matt 17w Emergency								17W	2200	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM22/DIM	DayLux™ Cylinder 5 Matt 17w DALI and Switch Dim								17W	2200	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM22/DIM/E3	DayLux™ Cylinder 5 Matt 17w DALI and Switch Dim & Emergency								17W	2200	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM32	DayLux™ Cylinder 5 Matt 25w								25W	3200	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM32/E3	DayLux™ Cylinder 5 Matt 25w Emergency								25W	3200	4000
Driver Fixed	IP 40	CRI 80	3.7 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM32/DIM	DayLux™ Cylinder 5 Matt 25w DALI and Switch Dim								25W	3200	4000
Driver DALI	IP 40	CRI 80	3.5 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM32/DIM/E3	DayLux™ Cylinder 5 Matt 25w DALI and Switch Dim & Emergency								25W	3200	4000
Driver DALI	IP 40	CRI 80	3.8 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		
DLCYM63	DayLux™ Cylinder 5 Matt 52w								52W	6300	4000
Driver Fixed	IP 40	CRI 80	3.4 Kg	Height 166mm	Width	Depth	Length	Dia 225mm	Cutout		

Matt and Gloss reflector options

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.