



Flood 7

Designed and engineered in the UK specifically to meet the requirements for sports lighting and to reduce light pollution levels. The Flood 7 is a high specification floodlight with a 70,000 hour lifespan, 7 year guarantee and 2 year on site warranty.

- Genuine replacement for 250/400/600W Metal Halide/Sodium Floodlight
- Perfect for sports, building façade's, landscape, security & car park lighting
- Asymmetric distribution, low light pollution (Asymmetric version)
- Up to 133 Lm/W
- Surge protected 10,000V (250/240W) & 4000V (80W) for lighting protection
- Cool White
- Aerodynamic, streamlined design for reduced windage
- Fully encapsulated IP66 TUV certified driver
- Nichia GRT-V1 LED / Meanwell Driver
- Long life 70,000 hours (L80 B10 @ 25°C)
- Robust construction IP66
- Standard universal mounting bracket
- Supplied pre-flexed (1.5M), tool free entry and construction for simple and quick installation
- Air pressure equalisation feature to eliminate capillary effect

Part Code	Description / Spec							Power	Lumens	Temp
DLF780S	DayLux™ Flood 7 80W Symmetric							80W	10000	4000
Driver Fixed	IP 66	CRI 80	4.6 Kg	Height 360mm	Width 265mm	Depth 82mm	Length	Dia	Cutout	
DLF780A	DayLux™ Flood 7 80W Asymmetric							80W	10000	4000
Driver Fixed	IP 66	CRI 80	4.6 Kg	Height 360mm	Width 265mm	Depth 82mm	Length	Dia	Cutout	
DLF78030	DayLux™ Flood 7 80W 30 degree							80W	10000	4000
Driver Fixed	IP 66	CRI 80	4.6 Kg	Height 360mm	Width 265mm	Depth 82mm	Length	Dia	Cutout	
DLF78015	DayLux™ Flood 7 80W 15 degree							80W	10000	4000
Driver Fixed	IP 66	CRI 80	4.6 Kg	Height 360mm	Width 265mm	Depth 82mm	Length	Dia	Cutout	
DLF7150S	DayLux™ Flood 7 150W Symmetric							150W	20000	4000
Driver Fixed	IP 66	CRI 80	6.8 Kg	Height 325mm	Width 413mm	Depth 83mm	Length	Dia	Cutout	
DLF7150A	DayLux™ Flood 7 150W Asymmetric							150W	20000	4000
Driver Fixed	IP 66	CRI 80	6.8 Kg	Height 325mm	Width 413mm	Depth 83mm	Length	Dia	Cutout	
DLF715030	DayLux™ Flood 7 150W 30 degree							150W	20000	4000
Driver Fixed	IP 66	CRI 80	6.8 Kg	Height 325mm	Width 413mm	Depth 83mm	Length	Dia	Cutout	
DLF715015	DayLux™ Flood 7 150W 15 degree							150W	20000	4000
Driver Fixed	IP 66	CRI 80	6.8 Kg	Height 325mm	Width 413mm	Depth 83mm	Length	Dia	Cutout	
DLF7240S	DayLux™ Flood 7 240W Symmetric							240W	30000	4000
Driver Fixed	IP 66	CRI 80	8.9 Kg	Height 418mm	Width 452mm	Depth 87mm	Length	Dia	Cutout	

Flood 7 cont.

Part Code	Description / Spec								Power	Lumens	Temp
DLF7240A	DayLux™ Flood 7 240W Asymmetric								240W	30000	4000
Driver Fixed	IP 66	CRI 80	8.9 Kg	Height 418mm	Width 452mm	Depth 87mm	Length	Dia	Cutout		
DLF724030	DayLux™ Flood 7 240W 30 degree								240W	30000	4000
Driver Fixed	IP 66	CRI 80	8.9 Kg	Height 418mm	Width 452mm	Depth 87mm	Length	Dia	Cutout		
DLF724015	DayLux™ Flood 7 240W 15 degree								240W	30000	4000
Driver Fixed	IP 66	CRI 80	8.9 Kg	Height 418mm	Width 452mm	Depth 87mm	Length	Dia	Cutout		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.