

Highbay 7

The Highbay 7 is a highly efficient versatile LED luminaire, ideally suited to a wide range of industrial applications for both new installations and retrofit applications.

- 1-10V dimming as standard
- Seoul Semiconductor LED
- Integrated microwave sensor versions available
- Sensor parameters can be set by optional remote control (sensor versions)
- High ambient temperature version also available on request
- Genuine Replacement for 250W/400W/600W Metal Halide or Sodium
- Perfect for warehousing, large retail and factories
- Emergency options available
- Self Test options available



Part Code	Description / Spec	Power	Lumens	Temp
DLHB100120	DayLux™ Highbay 7 120'	100W	14000	4000
Driver 1-10v IP 65 CRI 85 2.15 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout	
DLHB10090	DayLux™ Highbay 7 90'	100W	14000	4000
Driver 1-10v IP 65 CRI 85 2.15 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout	
DLHB150120	DayLux™ Highbay 7 120'	150W	21000	4000
Driver 1-10v IP 65 CRI 85 2.9 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout	
DLHB15090	DayLux™ Highbay 7 90'	150W	21000	4000
Driver 1-10v IP 65 CRI 85 2.9 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout	
DLHB200120	DayLux™ Highbay 7 120'	200W	28000	4000
Driver 1-10v IP 65 CRI 85 2.9 Kg Height 203mm Width Depth Length		Dia 280mm	Cutout	
DLHB20090	DayLux™ Highbay 7 90'	200W	28000	4000
Driver 1-10v IP 65 CRI 85 3.53 Kg Height 203mm Width Depth Length		Dia 280mm	Cutout	
DLHB100120/E3	DayLux™ Highbay 7 120' Emergency	100W	14000	4000
Driver 1-10v IP 65 CRI 85 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout	
DLHB10090/E3	DayLux™ Highbay 7 90' Emergency	100W	14000	4000
Driver 1-10v IP 65 CRI 85 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout	
DLHB150120/E3	DayLux™ Highbay 7 120' Emergency	150W	21000	4000
Driver 1-10v IP 65 CRI 85 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout	
DLHB15090/E3	DayLux™ Highbay 7 90' Emergency	150W	21000	4000
Driver 1-10v IP 65 CRI 85 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout	
DLHB200120/E3	DayLux™ Highbay 7 120' Emergency	200W	28000	4000
Driver 1-10v IP 65 CRI 85 Kg Height 203mm Width Depth Length		Dia 280mm	Cutout	

Highbay 7 cont.

Part Code	Description / Spec	Power	Lumens	Temp
DLHB20090/E3	DayLux™ Highbay 7 90' Emergency	200W	28000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 203mm Width Depth Length		Dia 280mm	Cutout
DLHB100120MW	DayLux™ Highbay 7 120' with MW Sensor	100W	14000	4000
Driver 1-10v IP 65 CRI 85	2.78 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout
DLHB10090MW	DayLux™ Highbay 7 90' with MW Sensor	100W	14000	4000
Driver 1-10v IP 65 CRI 85	2.78 Kg Height 173mm Width Depth Length		Dia 250mm	Cutout
DLHB150120MW	DayLux™ Highbay 7 120' with MW Sensor	150W	21000	4000
Driver 1-10v IP 65 CRI 85	3.53 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout
DLHB15090MW	DayLux™ Highbay 7 90' with MW Sensor	150W	21000	4000
Driver 1-10v IP 65 CRI 85	3.53 Kg Height 203mm Width Depth Length		Dia 250mm	Cutout
DLHB200120MW	DayLux™ Highbay 7 120' with MW Sensor	200W	28000	4000
Driver 1-10v IP 65 CRI 85	3.53 Kg Height 203mm Width Depth Length		Dia 280mm	Cutout
DLHB20090MW	DayLux™ Highbay 7 90' with MW Sensor	200W	28000	4000
Driver 1-10v IP 65 CRI 85	3.53 Kg Height 203mm Width Depth Length		Dia 280mm	Cutout
DLHB100120MW/E3	DayLux™ Highbay 7 120' with MW Sensor Emergency	100W	14000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 173mm Width Depth Length		Dia 250mm	Cutout
DLHB10090MW/E3	DayLux™ Highbay 7 90' with MW Sensor Emergency	100W	14000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 173mm Width Depth Length		Dia 250mm	Cutout
DLHB150120MW/E3	DayLux™ Highbay 7 120' with MW Sensor Emergency	150W	21000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 203mm Width Depth Length		Dia 250mm	Cutout
DLHB15090MW/E3	DayLux™ Highbay 7 90' with MW Sensor Emergency	150W	21000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 203mm Width Depth Length		Dia 250mm	Cutout
DLHB200120MW/E3	DayLux™ Highbay 7 120' with MW Sensor Emergency	200W	28000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 203mm Width Depth Length		Dia 280mm	Cutout
DLHB20090MW/E3	DayLux™ Highbay 7 90' with MW Sensor Emergency	200W	28000	4000
Driver 1-10v IP 65 CRI 85	Kg Height 203mm Width Depth Length		Dia 280mm	Cutout
DLHBPR	Highbay 7 Prismatic Reflector			
Driver IP CRI	Kg Height Width Depth Length		Dia	Cutout
DLHBAR	Highbay 7 Aluminium Reflector			
Driver IP CRI	Kg Height Width Depth Length		Dia	Cutout
DLHBRC	Highbay 7 Remote control programmer 15m Range			
Driver IP CRI	Kg Height Width Depth Length		Dia	Cutout

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.