



## Bollard 5

The DayLux Bollard 5 Range, available in 3 different wattages with root mounting kits provided as standard for secure fitting. Perfect for driveways and amenity lighting to ensure safe passage of visitors and staff. Sleek, modern design, powder coated aluminium construction coupled with the efficiency of LED means these units are 'fit and forget'.

- Clear polycarbonate diffuser
- Root mounting kit included
- Powder coated aluminium construction
- Choice of heights 500/700/1000mm
- Designed to minimise light pollution
- 360° Light distribution
- Warm White
- 30000 Hours



Part Code	Description / Spec								Power	Lumens	Temp
DLBOL6	DayLux™ Bollard 5 6W								6W	366	3000
Driver Fixed	IP 65	CRI 85	Kg	Height	500mm	Width	Depth	Length	Dia 120mm	Cutout	
DLBOL8	DayLux™ Bollard 5 8W								8W	605	3000
Driver Fixed	IP 65	CRI 85	Kg	Height	700mm	Width	Depth	Length	Dia 120mm	Cutout	
DLBOL10	DayLux™ Bollard 5 10W								10W	685	3000
Driver Fixed	IP 65	CRI 85	Kg	Height	1000mm	Width	Depth	Length	Dia 160mm	Cutout	

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.