

## Clean 5



Sealed LED luminaire to endure arduous environments.

High quality steel housing with welded frame and secured by Easy Fix style brackets.

Frame fitted with TP(a) rated diffuser providing excellent diffusion and outstanding light transmission.

Suitable for areas such as laboratories, hospitals, clean rooms, kitchens and showers.

LED lifespan L70 56,000 hours.



Part Code	Description / Spec	Power	Lumens	Temp
DLC5IP65	DayLux™ Clean 5 49W Cool White	49W	4660	4000
Driver Fixed IP 65 CRI 80 Kg Height 115mm Width 598mm Depth Length 598mm		Dia	Cutout	
DLC5IP65/E3	DayLux™ Clean 5 49W Cool White Emergency	49W	4660	4000
Driver Fixed IP 65 CRI 80 Kg Height 115mm Width 598mm Depth Length 598mm		Dia	Cutout	
DLC5IP65/DALI	DayLux™ Clean 5 49W Cool White DALI Dimmable	49W	4660	4000
Driver DALI IP 65 CRI 80 Kg Height 115mm Width 598mm Depth Length 598mm		Dia	Cutout	
DLC5IP65/DALI/E3	DayLux™ Clean 5 49W Cool White Emergency DALI Dimmable	49W	4660	4000
Driver DALI IP 65 CRI 80 Kg Height 115mm Width 598mm Depth Length 598mm		Dia	Cutout	

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.