

## Batten 7

The Batten 7 is a versatile general-purpose luminaire. With a sleek look, this Batten 7 is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.



- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Perfect for all commercial environments
- Tool-free termination
- Integrated controls
- Shatterproof
- Suitable for BESA Box mounting
- 8M detection range on corridor dim option (2.6m mounting height)
- 147 Lm/W



Part Code	Description / Spec								Power	Lumens	Temp
<b>DLBAT20</b>	<b>DayLux™ Batten 7 4ft 20W</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT20MS</b>	<b>DayLux™ Batten 7 4ft 20W with Microwave Sensor</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT20MSCD</b>	<b>DayLux™ Batten 7 4ft 20W with Microwave Sensor &amp; Corridor Dim</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT20/E3</b>	<b>DayLux™ Batten 7 4ft 20W Emergency</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT20MS/E3</b>	<b>DayLux™ Batten 7 4ft 20W Emergency with Microwave Sensor</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT20MSCD/E3</b>	<b>DayLux™ Batten 7 4ft 20W Emergency with Microwave Sensor &amp; Corridor Dim</b>								<b>20W</b>	<b>2850</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 69mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT40</b>	<b>DayLux™ Batten 7 4ft Twin 40W</b>								<b>40W</b>	<b>5360</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT40MS</b>	<b>DayLux™ Batten 7 4ft Twin 40W with Microwave Sensor</b>								<b>40W</b>	<b>5360</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT40MSCD</b>	<b>DayLux™ Batten 7 4ft Twin 40W with Microwave Sensor &amp; Corridor Dim</b>								<b>40W</b>	<b>5360</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT40/E3</b>	<b>DayLux™ Batten 7 4ft Twin 40W Emergency</b>								<b>40W</b>	<b>5360</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1230mm	Dia	Cutout		
<b>DLBAT40MS/E3</b>	<b>DayLux™ Batten 7 4ft Twin 40W Emergency with Microwave Sensor</b>								<b>40W</b>	<b>5360</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1230mm	Dia	Cutout		

**Batten 7 cont.**

Part Code	Description / Spec	Power	Lumens	Temp
DLBAT40MSCD/E3	DayLux™ Batten 7 4ft Twin 40W Emergency with Microwave Sensor & Corridor Di	40W	5360	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1230mm Dia Cutout			
DLBAT30	DayLux™ Batten 7 5ft 30W	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT30MS	DayLux™ Batten 7 5ft 30W with Microwave Sensor	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT30MSCD	DayLux™ Batten 7 5ft 30W with Microwave Sensor & Corridor Dim	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT30/E3	DayLux™ Batten 7 5ft 30W Emergency	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT30MS/E3	DayLux™ Batten 7 5ft 30W Emergency with Microwave Sensor	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT30MSCD/E3	DayLux™ Batten 7 5ft 30W Emergency with Microwave Sensor & Corridor Dim	30W	4410	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1530mm Dia Cutout			
DLBAT60	DayLux™ Batten 7 5ft Twin 60W	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT60MS	DayLux™ Batten 7 5ft Twin 60W with Microwave Sensor	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT60MSCD	DayLux™ Batten 7 5ft Twin 60W with Microwave Sensor & Corridor Dim	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT60/E3	DayLux™ Batten 7 5ft Twin 60W Emergency	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT60MS/E3	DayLux™ Batten 7 5ft Twin 60W Emergency with Microwave Sensor	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT60MSCD/E3	DayLux™ Batten 7 5ft Twin 60W Emergency with Microwave Sensor & Corridor Di	60W	7600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1530mm Dia Cutout			
DLBAT50	DayLux™ Batten 7 6ft 50W	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT50MS	DayLux™ Batten 7 6ft 50W with Microwave Sensor	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT50MSCD	DayLux™ Batten 7 6ft 50W with Microwave Sensor & Corridor Dim	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT50/E3	DayLux™ Batten 7 6ft 50W Emergency	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT50MS/E3	DayLux™ Batten 7 6ft 50W Emergency with Microwave Sensor	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT50MSCD/E3	DayLux™ Batten 7 6ft 50W Emergency with Microwave Sensor & Corridor Dim	50W	6350	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 69mm Depth Length 1795mm Dia Cutout			
DLBAT80	DayLux™ Batten 7 6ft Twin 80W	80W	10600	4000
Driver Fixed	IP 20 CRI 85 Kg Height 82mm Width 109mm Depth Length 1795mm Dia Cutout			

**Batten 7 cont.**

Part Code	Description / Spec								Power	Lumens	Temp
<b>DLBAT80MS</b>	<b>DayLux™ Batten 7 6ft Twin 80W with Microwave Sensor</b>								<b>80W</b>	<b>10600</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1795mm	Dia	Cutout		
<b>DLBAT80MSCD</b>	<b>DayLux™ Batten 7 6ft Twin 80W with Microwave Sensor &amp; Corridor Dim</b>								<b>80W</b>	<b>10600</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1795mm	Dia	Cutout		
<b>DLBAT80/E3</b>	<b>DayLux™ Batten 7 6ft Twin 80W Emergency</b>								<b>80W</b>	<b>10600</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1795mm	Dia	Cutout		
<b>DLBAT80MS/E3</b>	<b>DayLux™ Batten 7 6ft Twin 80W Emergency with Microwave Sensor</b>								<b>80W</b>	<b>10600</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1795mm	Dia	Cutout		
<b>DLBAT80MSCD/E3</b>	<b>DayLux™ Batten 7 6ft Twin 80W Emergency with Microwave Sensor &amp; Corridor Di</b>								<b>80W</b>	<b>10600</b>	<b>4000</b>
Driver Fixed	IP 20	CRI 85	Kg	Height 82mm	Width 109mm	Depth	Length 1795mm	Dia	Cutout		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.