

Flood 5



The Flood 5 LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- 10/20/30/50W Genuine replacement for Halogen Floodlights
- 70/100/150/200W Genuine replacement for Metal Halide Floodlights
- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR



Part Code	Description / Spec								Power	Lumens	Temp
DLF510	DayLux™ Flood 5 10W								10W	650	4000
Driver Fixed	IP 65	CRI 80	0.7 Kg	Height 140mm	Width 116mm	Depth 39mm	Length	Dia	Cutout		
DLF520	DayLux™ Flood 5 20W								20W	1500	4000
Driver Fixed	IP 65	CRI 80	1.1 Kg	Height 162mm	Width 142mm	Depth 42mm	Length	Dia	Cutout		
DLF530	DayLux™ Flood 5 30W								30W	2500	4000
Driver Fixed	IP 65	CRI 80	1.8 Kg	Height 183mm	Width 160mm	Depth 42mm	Length	Dia	Cutout		
DLF550	DayLux™ Flood 5 50W								50W	4000	4000
Driver Fixed	IP 65	CRI 80	2.1 Kg	Height 236mm	Width 186mm	Depth 57mm	Length	Dia	Cutout		
DLF570	DayLux™ Flood 5 70W								70W	7500	4000
Driver Fixed	IP 65	CRI 80	3.2 Kg	Height 320mm	Width 245mm	Depth 64mm	Length	Dia	Cutout		
DLF5100	DayLux™ Flood 5 100W								100W	9600	4000
Driver Fixed	IP 65	CRI 80	3.7 Kg	Height 320mm	Width 245mm	Depth 64mm	Length	Dia	Cutout		
DLF5150	DayLux™ Flood 5 150W								150W	15000	4000
Driver Fixed	IP 65	CRI 80	5.1 Kg	Height 380mm	Width 336mm	Depth 72mm	Length	Dia	Cutout		
DLF5200	DayLux™ Flood 5 200W								200W	20000	4000
Driver Fixed	IP 65	CRI 80	8 Kg	Height 380mm	Width 336mm	Depth 72mm	Length	Dia	Cutout		
DLF510P	DayLux™ Flood 5 10W PIR								10W	650	4000
Driver Fixed	IP 65	CRI 80	0.8 Kg	Height 230mm	Width 116mm	Depth 39mm	Length	Dia	Cutout		
DLF520P	DayLux™ Flood 5 20W PIR								20W	1500	4000
Driver Fixed	IP 65	CRI 80	1.2 Kg	Height 250mm	Width 142mm	Depth 42mm	Length	Dia	Cutout		
DLF530P	DayLux™ Flood 5 30W PIR								30W	2500	4000
Driver Fixed	IP 65	CRI 80	2 Kg	Height 270mm	Width 160mm	Depth 42mm	Length	Dia	Cutout		

Flood 5 cont.

Part Code	Description / Spec								Power	Lumens	Temp
DLF550P	DayLux™ Flood 5 50W PIR								50W	4000	4000
Driver Fixed	IP 65	CRI 80	2.4 Kg	Height 330mm	Width 186mm	Depth 57mm	Length	Dia	Cutout		
DLF570P	DayLux™ Flood 5 70W PIR								70W	7500	4000
Driver Fixed	IP 65	CRI 80	3.4 Kg	Height 400mm	Width 245mm	Depth 64mm	Length	Dia	Cutout		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.