

Downlight 7



The Downlight 7 is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Downlight 7 can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K
- Ideal for home and office environments
- Equivalent up to 2x26W fluorescent
- Anti-glare
- IP44 and IP65 options available
- Tool Free - Plug & Play
- Emergency downlights with 5 year battery guarantee available



Part Code	Description / Spec							Power	Lumens	Temp
DLDL944/E3	DayLux™ Downlight 7 Emergency							9W	910	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm	
DLDL1644/E3	DayLux™ Downlight 7 Emergency							16W	1660	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm	
DLDL2044/E3	DayLux™ Downlight 7 Emergency							20W	2250	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm	
DLDL944/DALI	DayLux™ Downlight 7							9W	910	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm	
DLDL1644/DALI	DayLux™ Downlight 7							16W	1660	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm	
DLDL2044/DALI	DayLux™ Downlight 7							20W	2250	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm	
DLDL944/DALI/E3	DayLux™ Downlight 7 Emergency							9W	910	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm	
DLDL1644/DALI/E3	DayLux™ Downlight 7 Emergency							16W	1660	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm	
DLDL2044/DALI/E3	DayLux™ Downlight 7 Emergency							20W	2250	CCT 3k/4k/6k
Driver DALI	IP 44	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm	
DLDL965	DayLux™ Downlight 7							9W	910	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm	
DLDL1665	DayLux™ Downlight 7							16W	1660	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm	

Downlight 7 cont.

Part Code	Description / Spec								Power	Lumens	Temp
DLDL2065	DayLux™ Downlight 7								20W	2250	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm		
DLDL965/E3	DayLux™ Downlight 7 Emergency								9W	910	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm		
DLDL1665/E3	DayLux™ Downlight 7 Emergency								16W	1660	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm		
DLDL2065/E3	DayLux™ Downlight 7 Emergency								20W	2250	CCT 3k/4k/6k
Driver Fixed	IP 65	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm		
DLDL965/DALI	DayLux™ Downlight 7								9W	910	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm		
DLDL1665/DALI	DayLux™ Downlight 7								16W	1660	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm		
DLDL2065/DALI	DayLux™ Downlight 7								20W	2250	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm		
DLDL965/DALI/E3	DayLux™ Downlight 7 Emergency								9W	910	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm		
DLDL1665/DALI/E3	DayLux™ Downlight 7 Emergency								16W	1660	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm		
DLDL2065/DALI/E3	DayLux™ Downlight 7 Emergency								20W	2250	CCT 3k/4k/6k
Driver DALI	IP 65	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm		
DLDL944	DayLux™ Downlight 7								9W	910	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 70.5mm	Width	Depth	Length	Dia 115mm	Cutout 90mm		
DLDL1644	DayLux™ Downlight 7								16W	1660	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 102mm	Width	Depth	Length	Dia 190mm	Cutout 160mm		
DLDL2044	DayLux™ Downlight 7								20W	2250	CCT 3k/4k/6k
Driver Fixed	IP 44	CRI 85	Kg	Height 117mm	Width	Depth	Length	Dia 250mm	Cutout 200mm		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.