

Disk 2



- Economic ultra-slim circular LED performance downlight
- Ideal for use in areas with shallow ceiling void
- Only suitable for semi commercial applications
- Remote driver with plug and play connection
- Edge lit providing excellent uniform illumination
- 10W comparable performance to 13W PLC 13W comparable performance to 18W PLC 19W comparable performance to 26W PLC
- LED lifespan L70 30,000 hours
- Non-dimmable



Part Code	Description / Spec								Power	Lumens	Temp
DLDSK10CW	DayLux™ Disk Downlight 2 10W Cool White								10W	534	4000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 136mm	Cutout 126mm		
DLDSK13CW	DayLux™ Disk Downlight 2 13W Cool White								13W	795	4000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 180mm	Cutout 168mm		
DLDSK19CW	DayLux™ Disk Downlight 2 19W Cool White								19W	1152	4000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 240mm	Cutout 228mm		
DLDSK10WW	DayLux™ Disk Downlight 2 10W Warm White								10W	534	3000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 136mm	Cutout 126mm		
DLDSK13WW	DayLux™ Disk Downlight 2 13W Warm White								13W	795	3000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 180mm	Cutout 168mm		
DLDSK19WW	DayLux™ Disk Downlight 2 19W Warm White								19W	1152	3000
Driver Fixed	IP 44	CRI 80	Kg	Height 25mm	Width	Depth	Length	Dia 240mm	Cutout 228mm		
DLDSK/E3	DayLux™ Disk Downlight 2 Self-test EM Pack										
Driver	IP	CRI	Kg	Height	Width	Depth	Length	Dia	Cutout		
DLDSK/BATT	DayLux™ Disk Downlight 2 Replacement Battery										
Driver	IP	CRI	Kg	Height	Width	Depth	Length	Dia	Cutout		

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.