

Panel 5 UGR

The back-lit Panel 5 LED panel boasts high lumen output and brightness whilst using the same power compared with an edge lit panel. With heat dissipation, the life of the panel LED chip is prolonged, making it ideal for installation into settings with heavy use such as schools, colleges and workplaces.



- High performance maintenance free LED panel
- Suitable for installation in offices, educational buildings, retail and healthcare premises
- Slimline design allows for installation into shallow ceiling voids
- TPa as standard
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- CCT selectable option also available
- Cool white, warm white and daylight options
- Panel Pod Self-Test emergency option
- Panel Pod sensor option
- Powered by Philips*
- LED lifespan L80 B10 54,000 hours
- Dimmable/OCTO options available



Part Code	Description / Spec							Power	Lumens	Temp
DLP5U28WW	DayLux™ Panel 5 UGR 28W Warm White							28W	3300	4000
Driver Fixed	IP 44	CRI 80	Kg	Height 36mm	Width 595mm	Depth	Length 595mm	Dia	Cutout	
DLP5U28CW	DayLux™ Panel 5 UGR 28W Cool White							28W	3300	4000
Driver Fixed	IP 44	CRI 80	Kg	Height 36mm	Width 595mm	Depth	Length 595mm	Dia	Cutout	
DLP5U28WW/DALI	DayLux™ Panel 5 UGR 28W Warm White DALI							28W	3300	4000
Driver DALI	IP 44	CRI 80	Kg	Height 36mm	Width 595mm	Depth	Length 595mm	Dia	Cutout	
DLP5U28CW/DALI	DayLux™ Panel 5 UGR 28W Cool White DALI							28W	3300	4000
Driver DALI	IP 44	CRI 80	Kg	Height 36mm	Width 595mm	Depth	Length 595mm	Dia	Cutout	
DLP5U/SK	DayLux™ Panel 5 UGR Suspension Kit									
Driver	IP	CRI	Kg	Height	Width	Depth	Length	Dia	Cutout	
DLP5U/SUR	DayLux™ Panel 5 UGR Surface Mounting Frame									
Driver	IP 20	CRI	Kg	Height 96mm	Width 601mm	Depth	Length 601mm	Dia	Cutout	

Guarantee and Warranty terms and conditions apply. Cover period starts from date of product supply.